



UKAS 008

Cantifix Limited

Unit 22, Garrick Industrial Centre,

Irving Way, London NW9 6AQ

13

203-CPR-06-2013

EN 14351 – 1:2006 + A1:2010

Windows (including roof windows) and external pedestrian doorsets without resistance to fire and / or smoke leakage

Aluminium and glass element for commercial and private buildings

<b>Project reference</b>	<b>Order number / Order name</b>
<b>Element reference</b>	<b>Item reference</b>
<b>System supplier</b>	<b>Cantifix Limited</b>
<b>System description</b>	<b>Silicone bonded fixed floor panel in a perimeter frame</b>

**\*\*NON-SERIES PRODUCT\*\***

<b>Thermal transmittance (W/m<sup>2</sup>K)</b>	<b>1.35 {&lt; 3.6m<sup>2</sup>}</b>
<b>Dangerous substances</b>	<b>NONE</b>
<b>Load bearing capacity of safety devices (N)</b>	<b>NONE FITTED</b>
<b>Ability to release (for escape doors only)</b>	<b>NONE FITTED</b>

Reaction to fire (class)	npd
External fire performance (class)	npd
Radiation properties	Light transmittance (%) npd Solar Gain (%) npd
Resistance to wind load (class)	npd
Resistance to snow (and permanent) loads (kN/m <sup>2</sup> )	npd
Impact resistance of glass (class)	Class A
Watertightness (class)	npd
Air permeability (class)	npd
Acoustic performance (dB)	npd

